

Creation of furrow

EDGING KERB

To create furrows for drainage.



MANUFACTURE

- Concrete composition: cement; sand; gravel; water; adjuvants.
- 2 kinds of finishings:
 - **Immediate demoulding** light bubbling is recommended for a better adherence. (Reference C001: standard edging kerb, only in immediate demoulding)
 - **Deferred demoulding** ('D') smooth concrete is recommended after crystallisation, remaining rough concrete.
- Grey concrete.

APPLICATION

- DRY SURFACE:
 - mechanical fastening and glue with a MS polymer adhesive.
 - Whenever the ground is painted before application or surface with crystallisation: gluing with MS Polymer and without mechanical fastening.
 - Drilling with Ø 8.160 twist drill.
- WET SURFACE:
 - Mechanical fastening and gluing with adhesive mortar (eg: CIMROC or similar).
 - Surface with crystallisation: gluing with adhesive mortar and without mechanical fastening.

BENEFITS

- Application over the ground: it doesn't interfere with concrete cover.
- Great to recover the water runoff from diaphragm walls.
- Durability.
- Can be painted.
- Sell with all the accessories.

PRODUCT INFORMATION

Reference	Designation	I (mm)	H (mm)	L (mm)	Unit weight (Kg Δ±5%)	Unit/ pallet	Weight/pallet (Kg Δ±5%)	Resistance and exposure class	Fixation	
C001	Immediate demoulding	Edging kerb 6	56	60	1000	6,2	150	950	C35/45, XC4	2 hammer fix 8x60
C002		Edging kerb 8	56	80	1000	9	100	920	C35/45, XC4	2 hammer fix 8x100
C003		Edging kerb 10	56	100	1000	10,6	90	980	C35/45, XC4	2hammer fix 8x120
C004		Edging kerb 5	45	50	1000	4.9	150	755	C35/45, XC4	2 hammer fix 8x80
C002D	Deferred demoulding	Edging kerb 8 D	56	80	1000	7,5	100	770	C35/45, XC4	2 hammer fix 8x100
C003D		Edging kerb 10 D	56	100	1000	10,9	90	1005	C35/45, XC4	2 hammer fix 8x120
C004D		Edging kerb 5 D	45	50	1000	4,5	150	685	C35/45, XC4	2 hammer fix 8x80

NB: Product liability is limited to the supplied product quality, and the guarantee ends whenever there's a misuse or a neglected use. All complaints concerning the appearance of the products must be done before application. We remind you that the application means that the product is fine.

