

Wall copings

**ROUND
TOP WALL
COPING**



MANUFACTURE

- Concrete composition: cement; sand; gravel; water; adjuvant.
- Wall coping made in reinforced concrete.

APPLICATION

Seal the coping to the wall with adhesive mortar or polymer. It is recommended to use adhesive between the copings. The distance between the wall and the coping edge must be equal or superior to 40mm.

BENEFITS

- Easy to install.
- Durability.
- Aesthetic.
- Available in grey and white.

PRODUCT INFORMATION

Reference	Designation	I x L	Dimensions (mm)				Unit weight (kg Δ±5%)	Unit / pallet	Wall (mm)	Resistance and exposure class
			e	i	H	h				
CH001	Round top wall coping 28	280 x 1000	30	220	60	40	30	30	150	C25/30, XC1
CH002	Round top wall coping 33	330 x 1000	30	270	60	40	35	20	200	C25/30, XC1
CH003	Round top wall coping 42	420 x 1000	30	360	65	55	53	20	300	C25/30, XC1
Wall coping with docking system										
CH004	Round top wall coping 34	340 x 1000	60	210	80	40	38	20	200	C25/30, XC1
CH005	Round top wall coping 34	340 x 1000	40	260	80	40	33	20	250	C25/30, XC1

NB: Product liability is limited to the supplied product quality, and the guarantee ends whenever there's a misuse or a neglected use. All complaints concerning the appearance of the products must be done before application. We remind you that the application means that the product is fine.

